



RY

RU

RML

	HP · CV · PS			KG		RY	RU	RML	Ø max cm	cm	A: cm B: cm
<b>speed RVM/260</b>	110-230	1000	1" 3/8 Z6	KG 1466	n. 6	n. 56	n. 28+56	n. 28	cm 8*	cm 3 – 9	A cm 255 - B cm 293
<b>speed RVM/290</b>	120-230	1000	1" 3/8 Z6	KG 1616	n. 6	n. 64	n. 32+64	n. 32	cm 8*	cm 3 – 9	A cm 290 - B cm 318
<b>speed RVM/320</b>	130-230	1000	1" 3/8 Z6	KG 1750	n. 6	n. 64	n. 32+64	n. 32	cm 8*	cm 3 – 9	A cm 320 - B cm 348

\* AVEC MARTEAUX

### Équipement de série

- Cardan (SH L =1100 SFT)
- Double attelage à 3 points avant / arrière cat. II/III
- Boîtier avec roue libre
- Patins latéraux réglables
- Rouleau arrière Ø 273 mm réglable
- Contre-couteaux à dents
- Tendeur automatique de courroies
- Déport latéral mécanique ou hydraulique
- 3 choix de couteaux
- Protections de sécurités « CE »

### Options

- Entraînement hydraulique avec moteur à pistons 30, 40, 60 ou 80 cc